

Facade Spotlight - Round

OSRAM LED Inside



POWER

• 16W • 38W • 58W

TECHNICAL SPECIFICATION

eclick LED Facade Spotlight

Power

16 W	38 W	58 W
3000 K / 4000 K / 6500 K / R / G / B		
Warm White / Neutral White / Cool White / Red / Green / Blue		
> 80		
830 / 840 / 865 / R / G / B		
1600 lm	3420 lm	5220 lm
100 lm / W	90 lm / W	90 lm / W
4D, 17D, 35D, 24Dx 43D, 35Dx 65D		

Optical Specification

- Color Temperature (CCT)
- Color
- Color Rendering Index (CRI)
- Color Code
- Luminous Flux
- Luminous Efficacy
- Beam Angle (50% lmax)

Electrical Specification

- Power Consumption
- Input Voltage
- LED Chip



16 W	38 W	58 W
240Vac / 24 Vdc		
Osram High Power LED		

Mechanical Specification

- Heatsink Material
- Lens Material
- PCB Material
- Operating Temperature
- Operating Humidity
- Ingress Protection

Cast Aluminium Base
PMMA
Sumitomo Metal Core PCB
- 20 °C ~ 50 °C
20 - 95 %RH
IP66

PRODUCT DIMENSION



PRODUCT RELIABILITY

Life Span of Product	> 40,000 hrs
70% Lumen Maintenance (L70)	> 40,000 hrs

[3000K]
[4000K]
[6500K]
[RED]
[GREEN]
[BLUE]

COLOUR OF LIGHT