

Modular Spot Eyeball

OSRAM LED Inside

POWER

- 7W
- 10W

TECHNICAL SPECIFICATION

eclick Modular Spot Eyeball

Type

2.5"

3.5"

Optical Specification

- Color Temperature (CCT)
- Color
- Color Rendering Index (CRI)
- Color Code
- Luminous Flux
- Luminous Efficacy
- Beam Angle

3000 K

Warm White

> 80

830

630 lm

900 lm

90 lm/W

24°

Electrical Specification

- Power Consumption
- Input Voltage (Normal)
- Input Frequency (Normal)
- Power Factor
- LED Chip
- LED Driver

7W

10W

170 - 265 Vac

50 / 60 Hz

> 0.9

Osram LED

Lifud Driver (Sirim)

Mechanical Specification

- Heatsink Material
- PCB Material
- Operating Temperature
- Operating Humidity
- Product Dimension
- Hole Size
- Ingress Protection

Die-cast Aluminium

Sumitomo Metal Core PCB

0°C - 40°C

20 - 90 %RH

65mm (Dia) x 73mm (H)

84mm (Dia) x 73mm (H)

54mm (Dia)

68mm (Dia)

IP20

PRODUCT RELIABILITY

Life Span of Product > 35,000 hrs

LED 70% Lumen Maintenance > 36,000 hrs

 COLOUR OF LIGHT [3000K]